

Technical Specification



Model #	American Collection-5.7MM
Grain	Deep Embossed
Plank Length	60 inches
Plank Width	7 1/4 inches or 9 inches for A501-9/A504-9/A505-9/A507-9
Plank Thickness	5.7mm (4.2mm Rigid Core + 1.5mm IXPE)
Wear Layer	0.5mm (20mil)
Edge	Square Edge
Sqft./ Box	7 ¼ " W=29.55 sq ft. & 9" W = 29.84 sq ft.
Locking System	Valinge System
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification



Model #	European Collection
Grain	Deep Embossed
Plank Length	60inches
Plank Width	9 ¼ inches
Plank Thickness	6.5mm (5mm Rigid Core + 1.5mm IXPE)
Wear Layer	0.5mm (20mil)
Edge	Painted Bevel
Sqft./ Box	22.73sq ft.
Locking System	Valinge System
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification



Model #	Metropolitan Collection-5MM
Grain	Deep Embossed
Plank Length	48 inches
Plank Width	9 ¼ inches or 7 ¼ inches for M754/M755
Plank Thickness	5mm (4mm Rigid Core + 1mm EVA)
Wear Layer	0.5mm (20mil)
Edge	Painted Bevel
Sqft./ Box	30.33sq ft. or 24.82sq ft. for M754/M755
Locking System	Valinge System
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification



Model #	Natural Plus Collection
Grain	Embossed in Register
Plank Length	60 inches
Plank Width	9 inches
Plank Thickness	6mm (5mm Rigid Core + 1 mm IXPE)
Wear Layer	0.5mm (20mil)
Edge	Micro Bevel
Sqft./ Box	22.50 sq ft.
Locking System	Unilin Uniclic System
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	15 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification



Model #	Paramount Collection
Grain	Deep Embossed
Plank Length	60 inches
Plank Width	9 ¼ inches
Plank Thickness	8mm (6mm Rigid Core + 2 mm IXPE)
Wear Layer	0.5mm (20mil)
Edge	Painted Bevel
Sqft./ Box	18.65 sq ft.
Locking System	Valinge System
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	15 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant