Technical Specification

American Flooring Distributor

Model #	American Collection, A501-512
Grain	Deep Embossed
Plank Length	60 inches
Plank Width	7-1/4 inches
Plank Thickness	5.7 mm (4.2 mm Rigid Core + 1.5 mm IXPE)
Wear Layer	0.5 mm (20 mil)
Edge	Pressed Edge
Sqft./ Box	29.55 sq ft
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	European Collection, E621-631
Grain	Deep Embossed
Plank Length	60 inches
Plank Width	9-1/4 inches
Plank Thickness	6.5 mm (5 mm Rigid Core + 1.5 mm IXPE)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	22.73 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & IIC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Metropolitan Collection, M741-756
Grain	Deep Embossed
Plank Length	48 inches
Plank Width	9-1/4 inches
Plank Thickness	5 mm (4 mm Rigid Core + 1 mm EVA)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	30.33 sq ft
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Natural Collection, N961-965
Grain	Deep Embossed
Plank Length	60 inches
Plank Width	9 inches
Plank Thickness	6 mm (4.5 mm Rigid Core + 1.5 mm EVA)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	22.50 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Natural Plus Collection, N971-979
Grain	Embossed in Register
Plank Length	60 inches
Plank Width	9 inches
Plank Thickness	6 mm (5 mm Rigid Core + 1 mm IXPE)
Wear Layer	0.5mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	22.50 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Paramount Collection, P851-858
Grain	Deep Embossed
Plank Length	60 inches
Plank Width	9-1/4 inches
Plank Thickness	8 mm (6 mm Rigid Core + 2 mm IXPE)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	18.65 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Builder's Choice Collection, BC-001-006
Grain	Deep Embossed
Plank Length	48 inches
Plank Width	7-1/4 inches
Plank Thickness	5 mm (4 mm Rigid Core + 1 mm EVA)
Wear Layer	0.3 mm (12 mil)
Edge	Micro Bevel
Sqft./ Box	29.00 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Beach Collection, B401-410
Grain	EIR
Plank Length	60 inches
Plank Width	9 inches
Plank Thickness	6.5 mm (5 mm Rigid Core + 1.5 mm EVA)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	22.28 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service

Technical Specification

American Flooring Distributor

Model #	Olympus Collection, O2501-2504
Grain	EIR
Plank Length	72 inches
Plank Width	9 inches
Plank Thickness	8mm (6.5 mm Rigid Core + 1.5 mm IXPE)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	27.14 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant

Technical Specification

American Flooring Distributor

Model #	Celestial Collection, C1201-1205
Grain	EIR
Plank Length	60 inches
Plank Width	9 inches
Plank Thickness	8 mm (6.5 mm Rigid Core + 1.5 mm IXPE)
Wear Layer	0.5 mm (20 mil)
Edge	Painted Bevel
Sqft./ Box	22.71 sq ft.
Locking System	Uniclic
Construction	100% waterproof. Rigid Core Vinyl (SPC Composite)
Installation Method	Floating
Sound Rating	STC 62 & llC 65
Indoor Air Quality	Low Emitting VOC's & Total VOC's, California & US
Residential Warranty	25 years
Commercial Warranty	10 years
Certification	FloorScore Certified by SCS Global Service, Emissions Dans Lair Intérieur: Class A+, CARB 2 compliant